



T 13/13

T11 | T13 | T13/13 | T16 TUMBLE DRYER



RADIAL AND AXIAL AIRFLOW
For maximal heat transfer, low energy consumption and short drying time



ECO VERSION
All dryers are available with reduced kW heating element



CLOUD - BASED PLATFORM
to easily monitor your laundry everywhere and at any time



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a 3 - year warranty

FEATURES & BENEFITS

Features	Options	Control
- Standard galvanized drum with large diameter - Large door opening for easy loading & unloading - Self cleaning lint screen	- Stainless steel drum - Stainless steel front - Reversing drum - Double door glass and insulation - Residual moisture control Sensodry: - safe drying of delicate linen - humidity detection in % - ideal in combination with SoftWash® - ideal for dry cleaners, fire depts - available on Easy and Full Control - WiFi kit - to order through Accessories	- Easy - To - Use Microprocessor (ECT) - intuitive control with simple selection of 3 programs - Full Control Programmer (FCT) - fully programmable timer with possibility of residual moisture control

TYPE		T11	T13	T13/13	T16
CAPACITY					
Capacity 1:18	kg (lb)	12(26)	16(35)	2x16(2x35)	19(42)
Capacity 1:22	kg (lb)	11(24)	13(29)	2x13(2x29)	16(35)
Drum volume	l	250	285	2x285	345
Drum diameter	mm	Ø 760	Ø 760	2xØ 760	Ø 760
AIRFLOW	m³/h	520	550	1050	600
DRYING AVERAGE	l/min.	190	225	2x225	300
MOTORS					
Fan	kW	0,55	0,55	2x0,75	0,55
Drive	kW	0,25	0,25	2x0,25	0,25
GAS HEATING					
Gas connection	NPT	1/2"	1/2"	2x1/2"	1/2"
Electrical connection		3x220 - 240V 50Hz, 1x220 - 240V 50Hz, 3x380 - 415V 50Hz			
Energy	kW	16,5	19,5	2x19,5	25
	kBTU/h	56,3	66,5	2x66,5	85,3
STEAM HEATING					
Steam connection	NPT	3/4"	3/4"	3/4"	3/4"
Electrical connection		3x220 - 240V 50Hz 1x220 - 240V 50Hz 3x380 - 415V 50Hz			
Steam output *	kW	16,5 - 22	19,5 - 27	2x19,5 - 27	22 - 32
Steam pressure	bar	3 - 6/7 - 10	3 - 6/7 - 10	3 - 6/7 - 10	3 - 6/7 - 10
ELECTRICAL HEATING					
Electrical connection		3x220 - 240V 50Hz, 3x380 - 415V 50Hz, 3x480V 60Hz			
Energy	kW	13,5	18,0	2x18,0	24,0
EXHAUST	mm	200	200	200	200
DIMENSIONS					
H×W×D	mm	1680x795x1070	1680x795x1160	2030x795x1240	1680x795x1280
Net weight	kg	230	250	370	250
TRANSPORT DATA					
Packed H×W×D	mm	1785x855x1100	1785x855x1190	2120x880x1325	1785x855x1310
Gross weight	kg	240	265	385	270

Technical drawings of the washing machine showing front, left, rear (steam), rear (gas), and rear (electric) views with dimensions and callouts.

- Front side:** Shows the front view with dimensions 1000 (height), 692 (width), and 795 (width). Callouts 1, 2, 3, and 4 point to specific features.
- Left side:** Shows the left side view with dimensions 1070 (T11), 1160 (T13), 1280 (T16), 1650 (height), 1675 (min. height), 1700 (max. height), and 1680 (height). Callout 5 points to the door.
- Rear side (Steam model):** Shows the rear view with dimensions 1135 (height), 145 (width), 184 (width), 180 (width), 190 (width), 200 (width), 285 (width), and 100 (width). Callouts 18 and 19 point to specific features.
- Rear side (Gas model):** Shows the rear view with dimensions 1150 (height), 145 (width), 184 (width), 180 (width), 190 (width), 200 (width), 285 (width), and 100 (width). Callouts 10, 11, 12, 13, 14, 15, and 17 point to specific features.
- Rear side (Electric model):** Shows the rear view with dimensions 1580 (height), 145 (width), 184 (width), 180 (width), 190 (width), 200 (width), 285 (width), and 100 (width). Callouts 10, 11, 12, 13, 14, 15, and 17 point to specific features.

- Primus preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding. www.primuslaundry.com